



Model	Capacity [Kg]	Speed [m/min.]	Kw	Chain Falls	A	A1	B	B1	B2	B3	B4	ØC	C1	C2	C3	D	D1	E	E1	F	ØG	G1	H	H1	H2	H3	L	M	N	P	ØR	S	ØT	Weight [Kg]
250W5	250	5	0,5	1	400	145	65	158	283	30	12	4	5	13,7	12	177	155	27	31	25	30	22	150	235	205	440	155	170	280	155	65	185	14	57
250W8	250	8	0,8	1	400	145	65	158	283	30	12	4	5	13,7	12	177	155	27	31	25	30	22	150	235	205	440	155	170	280	155	65	185	14	57
250W12	250	12	1	1	400	145	65	158	283	30	12	5	6	16,9	15	177	155	27	31	25	30	22	150	235	205	440	150	175	280	155	65	185	14	59
250W16	250	16	1	1	400	145	65	158	283	30	12	5	6	16,9	15	177	155	27	31	25	30	22	150	235	205	440	150	175	280	155	65	185	14	59
250W14	250	1-4	0,2-0,5	1	400	145	65	158	283	30	12	4	5	13,7	12	177	155	27	31	25	30	22	150	235	205	440	155	170	280	155	65	185	14	57
250W28	250	2-8	0,25-1	1	400	145	65	158	283	30	12	5	6	13,7	12	177	155	27	31	25	30	22	150	245	225	470	150	175	280	155	65	185	14	59
250W12	250	3-12	0,25-1	1	400	145	65	158	283	30	12	5	6	16,9	15	177	155	27	31	25	30	22	150	245	225	470	150	175	280	155	65	185	14	65