



Model	Capacity [Kg]	Speed [m/min.]	Kw	Chain Falls	A	A1	B	B1	B2	B3	B4	ØC	C1	C2	C3	D	D1	E	E1	F	ØG	G1	H	H1	H2	H3	L	M	N	ØR	S	ØT	ØV	Weight [Kg]
125V5	125	5	0,5	1	400	88	65	158	283	30	12	4	5	13,7	12	177	155	27	31	25	30	22	150	235	205	440	155	170	225	65	185	14	138	43
125V8	125	8	0,5	1	400	88	65	158	283	30	12	4	5	13,7	12	177	155	27	31	25	30	22	150	235	205	440	155	170	225	65	185	14	138	43
125V12	125	14	1	1	400	88	65	158	283	30	12	4	5	13,7	12	177	155	27	31	25	30	22	150	235	205	440	155	170	225	65	185	14	138	45
125V14	125	1-4	0,2-0,5	1	400	88	65	158	283	30	12	4	5	13,7	12	177	155	27	31	25	30	22	150	235	205	440	155	170	225	65	185	14	138	43
125V28	125	2-8	0,2-0,5	1	400	88	65	158	283	30	12	4	5	13,7	12	177	155	27	31	25	30	22	150	235	205	440	155	170	225	65	185	14	138	45
125V812	125	3,5-14	0,2-0,5	1	400	88	65	158	283	30	12	4	5	13,7	12	177	155	27	31	25	30	22	150	235	205	440	155	170	225	65	185	14	138	45